

Slut Prop:



Temperatur	Tryk
20 °C	20 bar
70 °C	10 bar
95 °C	6 bar
*20 °C	12 bar
*70 °C	6 bar
*95 °C	3 bar

Kan anvendes til: Rustfri, Fz, Alupex, Pex rør, Cu rør

FDA godkendt 

Varenr.	Rør UD	Farve	Antal pr. pose
PA7010610028 *	28mm	Hvid	10
PA7010610025	25mm	Blå	10
PA7010610022	22 mm	Hvid	10
PA7010610020	20 mm	Hvid	10
PA7010610018	18 mm	Sort	10
PA7010610016	16 mm	Hvid	10
PA7010610015	15 mm	Hvid	10
PA7010610012	12 mm	Hvid	10
PA7010610010 *	10 mm	Hvid	10

Låsering:



Varenr.	Rør UD	Farve	Antal pr. pose
PA701099RØ22	22	Rød	10
PA701099BL22	22	Blå	10
PA701099RØ20	20	Rød	10
PA701099BL20	20	Blå	10
PA701099GR18	18	Grå	10
PA701099RØ15	15	Rød	10
PA701099BL15	15	Blå	10
PA701099RØ12	12	Rød	10
PA701099BL12	12	Blå	10

Slut Prop:




Temperatur	Tryk
24 °C	19 bar
30 °C	16 bar
65 °C	10 bar
95 °C	6 bar

Kan anvendes til: Rustfri, Fz rør, Alupex, Pexrør, Cu rør

Varenr.	Rør UD	Farve	Antal pr. pose
SB7010610054	54mm	Messing	1
SB7010610042	42 mm	Messing	1
SB7010610035	35 mm	Messing	1

Afmonteringsværktøj:



Varenr.	Rør UD	Farve	Antal pr. pose
SB7010990054	54	Rød	1
SB7010990042	42	Rød	1
SB7010990035	35	Rød	1